

# KPC133D

## 21 LEDs Dome Camera



### ● FEATURES

- (1) High sensitivity in the dark environment, 0.05Lux / F2.0, 0 Lux (IR ON)
- (2) Excellent image quality
- (3) Day and night features for 24-hour surveillance
- (4) IR LED effective range reaches up to 15 meters

### ● SPECIFICATIONS\*

MODEL	KPC133D
Pick up Element	1/3" H.R. color CCD image sensor
Number of Pixel	512 (H) x 492 (V) <NTSC> / 512 (H) x 582 (V) <PAL>
Resolution	Standard
Min. Illumination	0.05Lux / F2.0, 0 Lux (IR ON)
IR LED	21 units
Effective Range	Up to 15 Meters
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.
Lens	f3.6mm / F2.0
Lens Angle	92.6°
IRIS Mode	AES
White Balance	ATW
Video Output	1.0 Vp-p composite, 75Ω
Power Source (±10%)	DC12V
Current Consumption (±10%)	90mA (IR OFF), 210mA (IR ON)

\* The specifications are subject to change without notice.

**Good Sensitivity in Low Illumination**

KPC13x Series



Conventional



**True Color**

KPC13x Series



Conventional



**Made in Taiwan**